


Panel Description PAC500AU TX and RX



- 1 Analogue audio left/right input/output

NOTE: PAC500AU TX/RX units can used as both a transmitter or receiver



- 2 CAT cable input/output

Specifications

PAC500AU TX and RX

- Audio Input/Output Connectors: 2x RCA analogue left/right
- CAT Input/Output Connectors: 1x RJ45
- Casing Dimensions (W x H x D): 79mm x 55mm x 24mm
- Dimensions including connections (W x H x D): 79mm x 63mm x 24mm
- Shipping Weight: 0.4kg
- Operating Temperature: 32°F to 104°F (0°C to 40°C)
- Storage Temperature: -4°F to 140°F (-20°C to 60°C)

NOTE: Specifications are subject to change without notice. Weights and dimensions are approximate.

Package Contents

PAC500AU

- 1x PAC500AU TX
- 1x PAC500AU RX
- 1x Quick Reference Guide

Maintenance

Clean this unit with a soft, dry cloth. Never use alcohol, paint thinner or benzene to clean this unit.

Certifications

FCC NOTICE

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

CAUTION - changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

CANADA, INDUSTRY CANADA (IC) NOTICES


This Class B digital apparatus complies with Canadian ICES-003. Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

CORRECT DISPOSAL OF THIS PRODUCT

This marking indicates that this product should not be disposed with other household wastes. To prevent possible harm to the environment or human health from uncontrolled waste disposal, recycle it responsibly to promote the sustainable reuse of material resources. To return your used device, please use the return and collection systems or contact the retailer where the product was purchased. They can take this product for environmentally safe recycling.

PAC500AU

Quick Reference Guide



Introduction

Our PAC500AU Audio over CAT cable extender transmits analogue audio signals up to distance of 500m. This plug and play device requires no power supply making it ideal for simple installations in which analogue audio needs to be extended over long distances.

FEATURES:

- Extend analogue audio signals up to distances of 500m over a single CAT cable
- Passive solution - Extender kit does not require a power supply

