

HEX11WPW-TX

HDMI Wall Plate HDBaseT™ Transmitter

Description

Our HEX11WPW-TX HDMI wall plate HDBaseT™ transmitter is a 4K solution that extends HDMI up to 70m 1080p (40m 4K). The HEX11WPW-TX has been designed to work with all Blustream HDBaseT™ receiver solutions, be installed in both UK and European backboxes and can be powered locally or from compatible Blustream HDBaseT™ products.


Specifications

- **Video Input Connectors:** 1 x HDMI Type A, 19-pin, female
- **Video Output Connectors:** 1 x HDBaseT™ RJ45 connector
- **RS-232 serial port:** 1 x 3-Pin Phoenix connector
- **IR Input port:** 1 x 3-Pin Phoenix connector
- **Local power input:** 1 x 2-Pin Phoenix connector
- **Casing Dimensions (W x H x D):** 146mm x 86mm x 46mm
- **Operating Temperature:** 32°F to 104°F (-5°C to +55°C)
- **Storage Temperature:** -4°F to 140°F (-25°C to +70°C)
- **Power Supply:** 12V/1A DC

Key Features

- Advanced HDBaseT™ technology offering distribution of video and audio over a single CAT cable
- Supports 4K UHD video up to 40m (3840 x 2160 @30Hz 4:4:4, 4096 x 2160 @24Hz 4:4:4, and 4K @60Hz 4:2:0)
- Extends HDMI 1080p up to a distance of 70m
- Supports all known HDMI audio formats including Dolby TrueHD, Dolby Atmos, Dolby Digital Plus and DTS-HD Master Audio transmission
- Supports 12V-48V PoC from compatible Blustream HDBaseT™ Matrix or Receivers
- Bi-directional RS-232 pass through
- Supports IR pass-through to HDBaseT™ Matrix or Receiver
- Compatible with all Blustream HDBaseT™ Matrix or Receivers*
- Magnetic faceplate surround allowing both UK & EU backbox compatibility
- HDCP 2.2 support

*Technical performance is subject to the features supported on the connected HDBaseT™ product



Blustream cannot be held responsible for errors in typography or photography. Specifications are subject to change without notice.